Admonter
NATURE´S FAVOURITE DESIGNER

PINE

FLOORS

Initial care - with Admonter maintenance oil
You can find more information in the Admonter care- and laying instructions and at www.admonter.eu/en/downloads/

Admonter FLOORs on under-floor-heating-system
Admonter FLOORs are ideally suited for under-floor heating systems.
We recommend hot-water underfloor heating systems set at low temperature. The surface temperature of 29°C must not be exceeded.
We suggest that our products ideally are fully glued down for best results with Admonter elastic adhesive.

However, like all engineered boards our planks can be laid as a floating installation (except 2-layer floors and 3-layer floors small (SF-RS), they have to be fully glued down).

More information at www.admonter.at or contact your specialist dealer.

Skirting: Typ1, Typ3, Typ3 white, Typ4

Grading	Thickn. mm	Width mm	Length mm (subject to availability)	Installation and construction			Surface	Texture
				Tongue & groove		lock-it		
basic	15	161	1850/2000	-	3-layer NH-RS	3-layer NH-RS	natural oil	sanded

Technical information							
Wood species	Thickness mm	Weight (kg/m²)	Moisture content (%)	Lambda	d-Value	Hardness	Fire classification
Pine	15	7,5	8+/-2	0,14	0,107	19	F_{fl}

LH-RS: Hardwood-backing / **NH-RS:** Softwood-backing
SF-RS: Softwood-veneer-backing, **ng:** natural oiled / **uv:** UV oiled / **ml:** matt lacquer

For more information visit our
website **www.admonter.at**

A brand of STIA Holzindustrie GmbH, Sägestrasse 539, 8911 Admont, Austria
Errors and changes possible, phone: +43(0)3613/3350-0, fax: +43(0)3613/3350-119, info@admonter.at, www.admonter.at

February 2016

Admonter flooring is a 100 % natural product. A picture is never a substitute for the „real thing". For this reason we recommend a visit to your nearest Admonter flooring dealer. He will be pleased to show you samples.